



GENERAL SPECIFICATIONS

• L.O.A	6,40 m	21'
• Hull length	6,25 m	20'6"
• L.W.L.	6,00 m	19'8"
• Beam	2,48 m	8'2"
• Lifting keel version	0,70 - 1,80 m	2'4" - 5'11"
• Lifting keel version ballast weight	300 kg	661 lbs
• Air draught	9,50 m	31'2"
• Light displacement	1 245 kg	2,745 lbs
• Engine power outboard max	8 Kw - 10 HP	10 HP
• Transportable road gauge		

ARCHITECTS

- Finot Conq And associates

CE CERTIFICATION

- Category C - 6 people
- Category D - 6 people

STANDARD SAIL LAYOUT AND AREA

• Mainsail	15,8 m ²	170 sq ft
• Genoa 97 %	6,98 m ²	75 sq ft
• Asymmetrical spinnaker	24,6 m ²	265 sq ft
• Code 0	15 m ²	161 sq ft
• I	7 m	23'
• J	2,37 m	7'9"
• P	7,40 m	24'3"
• E	3,15 m	10'4"

STANDARD EQUIPMENT

CONSTRUCTION

Design in accordance with European Directive requirements and according to CE certification.

- Monolithic hull design in polyester
- Structural counter moulding made with unidirectional fabrics laminated and stuck evenly to the hull
- Deck made of injection moulding (Fibreglass sandwich / Balsa wood / Polyester resin)
- Accessible areas covered in a «Picot» type non-slip surface
- Hull-deck join screwed, bonded and trimmed with 1 bulwark
- Cast iron keel, pivoted and adjusted with a manual system of lifting screw and handle. Mounted with adjustable plates
- 2 retractable polyester rudders with sleeve system
- White coloured hull - Decoration dark grey

DECK EQUIPMENT

RIGGING

- Deck-stepped, freestanding aluminium anodised mast, single spreaders
- Anodised aluminium boom
- Discontinuous stainless steel standing rigging and Dyform
- Shroud chain plates fixed to hull-deck joint
- 1 mainsail tackle mounted on snap shackle in cockpit bottom
- 1 Adjustable boom vang by hoist
- 1 trimming tackle on boom
- Genoa furler
- 2 genoa sheet tracks with back and forth adjustable bearing cars
- Rigging run back to cockpit
- Complete running rigging: 1 Genoa furler line, 1 Genoa halyard, 1 Main halyard, 1 Reef line
- 2 cheek blocks
- 4 clutches
- 1 Jam cleat
- 2 Belaying cleats
- 2 Jamming cleats

WINCHES

- 2 aluminium winches (H08A): Genoa sheet, Halyards and Reef line
- 1 Winch handle

MOORING LINES - MOORING

- Self-draining chain locker
- 1 Stainless steel bow fitting 1 stainless steel bow roller
- 4 Aluminium mooring cleats

SAFETY ON DECK

- 1 stainless steel 3 leg pulpit
- 2 Stainless steel pushpits
- Stainless steel single guardrails and stanchions

COCKPIT

- Self-draining cockpit
- 2 wet lockers with locks
- 2 solid wood footrests on cockpit benches
- Solid wood tiller with jointed extension
- Benches cockpit polyester

AFT TRANSOM

- 1 Stainless steel bathing ladder
- 1 handhold

INTERIOR

- Woodwork: Light Alpi teak
- White ceruse oak laminate flooring, Polyester, Non-slip
- Vinyl fabric spar ceiling on deck counter-moulding
- PVC Arredo upholstery

COMPANIONWAY

Headroom: 1,45 m / 4'9"

- 1 sliding companionway hatch with fitted window

FORWARD CABIN

- Double bed (1,90 m x 1,40 m / 6'3" x 4'7") - Foam mattress with cover
- 1 circular opening deck hatch

GALLEY

- Storage

SALOON

Headroom: 1,45 m / 4'9"

- 2 bench seats / Single berths (2,20 m x 0,60 m / 7'3" x 2') with mattress and cover
- Storage
- 2 oilskins pegs
- 2 fixed hull portholes

ELECTRICITY

- 1 12 V 50 Amp battery
- 1 12 V electrical and 6 function panel with fuses
- Navigation lights
- Lighting: Ceiling lights and lamp fittings

PLUMBING

- 1 Manual bilge pump

SERIES

	PERFORMANCE
• 1 Dacron square top mainsail	■
• 1 Dacron jib on roller furling	■
• Code 0 on "Top Down" furling system	■
• Asymmetrical spinnaker rigging	■
• Lazy bag + Lazy jack	■
• Bowsprit Polyester	■
• Steering compass on partition	■
• Natural solid wood slatted cockpit benches	■
• Opening cockpit locker hatch	■
• 1 Outboard engine bracket (30 kg / 66 lbs max)	■

PACKS

ELECTRONIC TACKTICK/RAYMARINE PACK

- Cockpit: Wireless multi-function display, Log, Speed, Depth and Temperature

OTHER OPTIONS

- Asymmetrical spinnaker
- Windex Windvane
- Fold-down mast kit
- Beaching legs brackets
- Beaching legs
- Folding saloon or cockpit table
- Chemical toilet
- Fresh water system - Reserve 35 L / 9 US Gal - Hand pump - Galley: Sink with drain
- 4 removable storage nets on stainless steel rails along hull
- Grey hull
- Electric engine